


PETIT SC. By SCHELL.



PETIT SC.

Thanks to their all-metal design, SCHELL PETIT SC self-closing fittings are particularly robust and are characterised by a low water consumption. Sophisticated technology and quality "Made in Germany" at an attractive price. All of which makes PETIT SC a genuine model of success.





SCHELL self-closing wash basin tap PETIT SC

For high-pressure cold and pre-mixed water Robust single-hole tap in a vandal-proof all-metal construction with plastic cartridge manual actuation and automatic closing function Comprises:

Mounting accessories for single-hole installation

Range of use / technical specifications:

• Flow pressure: 1 to 5 bar

• Flow time: approx. 7 s (no flow time adjuster)

Material: Housing made of DIN EN brass Flow rate: 6.0 l/min at 3 bar flow pressure Dimensions: DN 15 G 1/2 ext. thread chrome, PU 1 order No.: 02 122 06 99

Material: Housing made of dezincification-resistant brass Flow rate: 5.0 l/min at 3 bar flow pressure Dimensions: DN 15 G 1/2 ext. thread chrome, PU 1 order No.: 02 130 06 99



SCHELL GmbH & Co. KG Valve Technology Raiffeisenstraße 31 57462 Olpe Germany Tel. +49 2761 892-0 Fax +49 2761 892-199 info@schell.eu www.schell.eu



SCHELL PETIT SC self-closing wall-mounted tap

HD-K (High-pressure cold or pre-mixed water)

Robust wall-mounted tap in a vandal-proof all-metal construction with plastic cartridge

manual actuation and automatic closing function

Comprises:

 PETIT SC self-closing wall-mounted tap with rosette Ø 60 mm

Range of use / technical specifications:

- Flow control 5.0 l/min, irrespective of pressure
- Flow pressure: 0,8 5 bar
- Flow time: adjustable between 6 15 s (preset to 7 s)

Material: Housing made of dezincification-resistant brass Dimensions: G 1/2 ext. thread chrome, PU 1

order No.: 02 136 06 99

With isolating valve

Dimensions: G 1/2 ext. thread chrome, PU 1

order No.: 02 147 06 99

Accessories: Extension 60 mm

order No.: 61 662 06 99



